

SENSORI PER SINGOLE FUNI



QL-EOS-R

QL-EOS-R V.3 (RH-HC)

QL-EOS-R V.2 (RH-SM)

	QL-EOS-R	QL-EOS-R V.3 (RH-HC)	QL-EOS-R V.2 (RH-SM)
Diametro fune	da 4mm a 16 mm	da 6mm a 16 mm	da 6mm a 16 mm
Carico nominale	2000 Kg	1000 Kg	750 Kg
Sovraccarico massimo	4000 Kg	5000 Kg	1000 Kg
Dimensioni	125 x 52 x 34 mm	110 x 65 x 24,5 mm	47,5 x 20 x 10\ mm
Lunghezza cavo	3m / 5m	1.8m	1.8m

SENSORI SOTTO CABINA - ARCATA - MULTI FUNI



QL-EOS-B

QL-EOS-B1

QL-EOS-R1 A100/A200/A300

	QL-EOS-B	QL-EOS-B1	QL-EOS-R1 A100/A200/A300
Diametro fune			da 6mm a 23 mm
Carico massimo	800 Kg	3000 Kg	3000 / 3000 / 4500 Kg
Sovraccarico massimo	2000 Kg	6000 Kg	6000 6000 / 9000 Kg
Dimensioni	190 x 47,5 x 45 mm	130 x 31,8 x 31,8 mm	208 x (157/230/306) x (103/133) mm
Lunghezza cavo	1,8m	1,8m	1,8m

	R1 A-100	R1 A-200	R1 A-300
Lunghezza (A)	208 mm	208 mm	208 mm
Larghezza (B)	157 mm	230 mm	306 mm
Profondità (C)	103 mm	133 mm	133 mm
Distanza max funi	114 mm	187 mm	264 mm

